

PRODUCT DATASHEET

DULUX D 26 W/865

OSRAM DULUX D | CFLni, 2 tubes, with 2-pin base for CCG operation



AREAS OF APPLICATION

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

PRODUCT BENEFITS

- Extremely economical
- Good quality of light
- Excellent luminous flux
- Long service life
- Improved maintenance

PRODUCT FEATURES

- Color rendering index $R_a : \geq 80$
- Short and compact pin-base lamp with double-turn tubes
- Single-ended two-pin plug-in G24d base



TECHNICAL DATA


Electrical data

Nominal voltage	105 V
Rated wattage	27.30 W
Nominal wattage	27.30 W
Nominal current	0.35 A

Photometrical data

Nominal luminous flux	1600 lm
Luminous flux at 25 °C	1710 lm
Rated luminous flux	1600 lm
Rated color temperature	6500 K
Color rendering index Ra	≥80
Rated LLMF at 2,000 h	0.77
Rated LLMF at 4,000 h	0.70
Rated LLMF at 6,000 h	0.69
Rated LLMF at 8,000 h	0.68
Light color (designation)	LUMILUX Cool Daylight
Color temperature	6500 K
Luminous flux	1600 lm
Color rendering index Ra	≥80

Dimensions & weight



Diameter	12.0 mm
Overall length	172.0 mm
Length	172.0 mm
Length acc. to IEC standard	160 mm
Length with base excl. base pins/connection	149.00 mm
Outer bulb	T12X2

Maximum diameter	11.0 mm
-------------------------	---------

Lifespan

Nominal lamp life time	10000 h
Rated lamp life time	10000 h
Service life	6500 h
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.95
Rated lamp survival factor at 8,000 h	0.81
Operation mode LLMF/LSF	50 Hz
Lifespan	10000 h ¹⁾

¹⁾ With CCG/LLCG

Additional product data

Base (standard designation)	G24d-3
Mercury content	1.6 mg

Capabilities

Dimmable	No
Suitable for indoor	Yes


Certificates & standards

Energy consumption	32 kWh/1000h
Energy efficiency class	G

Country-specific categorizations

ILCOS	FSQ-26/865-I-G24d-3
--------------	---------------------

Light Distribution



Spectral power distribution

EQUIPMENT / ACCESSORIES

- Suitable for operation on conventional control gear

SAFETY ADVICE

In case of lamp breakage: www.ledvance.com/brokenlamp

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300486987	Folding carton box 1	180 mm x 36 mm x 36 mm	63.00 g	0.23 dm ³
4050300486994	Shipping carton box 10	192 mm x 119 mm x 155 mm	694.00 g	3.54 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.