

# SLW2300

## PIR Light Controller – White

### Features & Benefits

- Pan and tilt feature
- Light ON times adjustable
- LUX (light level) adjustment – Day to Night
- Manual ON/OFF switching override
- IP55 weatherproof rating
- Simple and quick to fit terminal block connectors
- Corner mounting bracket available – SLWCB (Sold Separately)



### Technical Data

|                              |   |
|------------------------------|---|
| Operating Voltage            | 230V AC   |
| Frequency                    | 50Hz  |
| Installation Type            | Surface   |
| Earth Class Rating           | Class I   |
| Operating Temperature        | -20°C to 40°C   |
| Ingress Protection Rating    | IP55  |
| Setting Type                 | Dial  |
| Approved Mounting Height (m) | 2.5   |
| Motion Detection (m)         | 12  |
| Detection Angle              | 180°  |
| Pan & Tilt Adjustment        | 90° Left/Right From Centre, Tilt 15° (Up), 60° (Down) |
| Mounting Hole Centres (mm)   | 50  |
| Standby Consumption          | <1W   |
| Number Of Channels           | 1   |

# Data sheet

## SLW2300

Light / PIR Lighting Controllers

|                              |   |
|------------------------------|---|
| <b>Switch Rating</b>         | 250W LED, 500W Fluorescent, 2300W Halogen |
| <b>ON Time Adjustment</b>    | 5 Seconds to 15 Minutes. User Adjustable  |
| <b>LUX Level</b>             | 5 to 1000                                 |
| <b>Detection Range (m)</b>   | 12  |
| <b>Permanent ON Facility</b> | Yes (Pulse Override)                      |
| <b>Dusk Till Dawn</b>        | No  |
| <b>Multiple Unit Support</b> | Up to 4 Units In Parallel                 |
| <b>Cable Entry(s)</b>        | Back Entry, Bottom Entry                  |

### General

|                                    |                               |
|------------------------------------|-------------------------------|
| <b>Weight (g)</b>                  | 193                           |
| <b>Height (mm)</b>                 | 95                            |
| <b>Width (mm)</b>                  | 78                            |
| <b>Depth (mm)</b>                  | 141                           |
| <b>Body Construction</b>           | Polycarbonate                 |
| <b>Product Colour</b>              | White                         |
| <b>Accessories (Included)</b>      | Fittings (Rawl Plugs, Screws) |
| <b>EAN Number</b>                  | 5012483013212                 |
| <b>Guarantee Period</b>            | 3 Years                       |
| <b>Trade Tariff Commodity Code</b> | 8536508090                    |

### Line Diagrams

