

## Fittings / LED Bulkheads

# Universal Wattage Switchable LED Gear Tray - Emergency



Our Universal Wattage Switchable LED Gear Tray is colour selectable as standard, providing a versatile solution for the user to upgrade existing bulkheads.

- Retrofit Gear Tray for 16/28/32W 2D fittings.
- 3 CCT (3/4/6000K).
- Emergency & sensor versions available.
- 30000 hours.
- 3-year warranty.

## Technical Specification

|                     |       |
|---------------------|-------|
| <b>Product Code</b> | 11607 |
|---------------------|-------|

### Reference

|                  |         |
|------------------|---------|
| <b>Guarantee</b> | 3 Years |
|------------------|---------|

|            |               |
|------------|---------------|
| <b>EAN</b> | 5013588116075 |
|------------|---------------|

|                       |            |
|-----------------------|------------|
| <b>Commodity Code</b> | 9405423990 |
|-----------------------|------------|

|                          |    |
|--------------------------|----|
| <b>Country of Origin</b> | CN |
|--------------------------|----|

## Technical Specification

|                                |                |
|--------------------------------|----------------|
| Watts (W)                      | 9/14/18        |
| Equivalent Watts (W)           | 33/51/62       |
| Volts (V)                      | 220/240        |
| Colour Temp (K)                | 3000/4000/6000 |
| Lumens (lm)                    | 1200/1800/2200 |
| Lumens per Watt (lm/W)         | 122-133        |
| Candelas (cd)                  | 490-910        |
| CRI (ra)                       | 85             |
| Frequency (Hz)                 | 50             |
| LED Drive Current              | 130mA          |
| Energy Consumption (kWh/1000h) | 18             |
| Life Hours                     | 30000          |
| Switching Cycles               | 30000          |
| Energy Rating                  | C              |
| Dimmable?                      | No             |

## Dimensions

|             |       |
|-------------|-------|
| Height (mm) | 240.5 |
| Width (mm)  | 237   |
| Depth (mm)  | 49    |

## Packaging Information

|                                |         |
|--------------------------------|---------|
| Height (mm)                    | 240.5   |
| Width (mm)                     | 237     |
| Depth (mm)                     | 49      |
| Individual Product Weight (kg) | 0.31    |
| Single Carton Height (mm)      | 50      |
| Single Carton Width (mm)       | 272     |
| Single Carton Depth (mm)       | 256     |
| Single Carton Weight (kg)      | 0.457   |
| Individual Volume              | 0.00348 |
| Inner Box Qty                  | 1       |
| Outer Box Qty                  | 10      |
| Outer Box Height (mm)          | 280     |
| Outer Box Width (mm)           | 550     |
| Outer Box Depth (mm)           | 295     |
| Outer Box Weight (kg)          | 4.9     |
| Outer Box Volume               | 0.04543 |